



INNOVATIVE
**HEAT & SOUND
CONTROL**
SOLUTIONS

FAQ'S JEEP HEADLINER KITS

Do I need to remove the hard top to install the headliner kit?

It is highly recommended to remove the top to install. The front Freedom tops can be easily removed and headliner kit installed. The rear hard tops are difficult to access and get pieces of headliner kit lined up properly and installed. It is highly recommended to remove the top to install.

Does the top need to be clean to install?

Yes. The underside of all hard top pieces need to be very clean for proper adhesion and long term use.

Do the grooves in the hard top pieces need to be filled in?

Yes. Each kit comes with foam strips that get installed into the grooves to fill them in before each headliner piece is installed. This gives the headliner a smooth finish when installed.

Can the headliner pieces be cleaned?

Yes. The headliner pieces can be gently wiped with a damp cloth to be cleaned. Too much pressure or a chemical cleaner might damage the textured surface. But they can be wiped with a damp cloth to be cleaned.

How long does it take before I can drive my JEEP after install?

We recommend keeping the hard top pieces inverted and letting the pieces adhere properly for at least 25 minutes for the adhesive to set properly.

Do I need to trim any of the pieces to fit?

No. Every kit is 3D scanned and cut on CNC table to ensure a proper fitment per year and model.

**FOR ANY QUESTIONS NOT COVERED IN OUR FAQ'S, PLEASE CONTACT US DIRECTLY.
CALL 800-264-9472 OR VIA EMAIL AT TECH@DESIGNENGINEERING.COM**