



## Frequently Asked Questions

### DEI Fire Wrap 3000™

#### ***What is it made of?***

Fire Wrap 3000 is made of a woven insulated glass fiber braided sleeve heavily coated with an iron oxide silicone rubber. We have added a hook and loop closure for ease of installation. This means that you will not need to pull the line, wire, or hose off. Just simply wrap the product around the problem area.

#### ***What temperatures can it withstand?***

Fire Wrap 3000 can withstand five hundred degrees F continuous and two thousand degrees F intermittent heat.

#### ***Can the material be cut?***

Yes, Fire Wrap 3000 is easily cut to size. Scissors are a good tool to use but anything sharp will cut the material.

#### ***What sizes can I get the wrap in?***

There are three to choose from. Five eighths of an inch, one inch, and one and a half inches are the diameters. The material comes in a two foot length section.

#### ***How can I seal the ends?***

Fire tape is the best method for sealing this product. It is a non-adhesive silicone rubber tape that is self-bonding, self-curing, and forms a permanent water-tight barrier. This will help isolate the heat inside the Fire Wrap 3000 and also aid in keeping dirt and chemicals out.

Design Engineering Inc.  
604 Moore Road  
Avon Lake, OH 44012  
[www.DesignEngineering.com](http://www.DesignEngineering.com)  
**(800)264-9472**

v05.06  
FAQ015