

## PRODUCT INSTRUCTIONS

Thank you for purchasing genuine Design Engineering, Inc. products. Be sure to always wear the proper safety equipment when installing any DEI product. Design Engineering, Inc. WILL NOT BE HELD LIABLE FOR IMPROPER INSTALLATION OR USE OF THIS PRODUCT. Please follow all instructions provided. If you are unsure of any installation procedure, please contact a certified technician.

**DESCRIPTION:** Tie Tool Extension, 1/4" Drive

**PART NUMBER:** 010220

**APPLICATION(s):** For tightening Stainless Steel Locking Ties

**KIT CONTENTS:**  
Locking Tie Tool (1)

**TOOLS NEEDED:** 1/4" drive handle or ratcheting socket driver, 1/4" extension (optional), and side cutters.

**ADDITIONAL INFORMATION:** This tool is designed to work with all types of metal locking ties up to 12mm wide.



Fig. 1



Fig. 2

1. Begin initially tightening the tie using hands or pliers. Be careful as the sides of the metal ties can be sharp. **Figure 1**
2. Insert the slotted tool through the tie just after the clasp. **Figure 2**

**TOP TIP:** Working in small space? No problem, slide the tool onto any 1/4" drive extension to give your hands some extra room. Great when tying exhaust wrap near cylinder heads.

3. Twist the tie away from the locking clasp.. **Figure 3**
4. Remove slot tool.
5. Trim excess tie using side cutters, fold under, and crimp. **Figure 4**

**TOP TIP:** DEI recommends using a hand driver because of better torque control and a reduced risk of over tightening. However, a ratcheting socket driver will also work with this tool.

(Continued on back)



Fig. 3



Fig. 4