

SAFETY DATA SHEET

Date Prepared : 05/21/2015

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: Black Butyl mastic extrusion on release carrier**PRODUCT CODE:** 050199, 050200, 050202, 050204, 050206, 050210, 050212, 050214, 050221, 050222, 050223, 050224**MANUFACTURER**

Design Engineering, Inc.
604 Moore Rd. Avon Lake Ohio 44012
Customer Service: 440-930-7940
email: sales@designengineering.com

Emergency telephone number:
800-264-9472

2. HAZARDS IDENTIFICATION

GHS LABEL

No labeling applicable

EMERGENCY OVERVIEW**PHYSICAL APPEARANCE:** Black mastic.**IMMEDIATE CONCERNS:** May cause skin or eye irritation after repeated or prolonged contact.**POTENTIAL HEALTH EFFECTS****EYES:** Contact may cause eye irritation.**SKIN:** Prolonged or repeated contact may cause skin irritation. Contact with heated product may result in burns.**SKIN ABSORPTION:** None Expected.**INGESTION:** Not a likely route of entry.**INHALATION:** Not a likely route of entry.**COMMENTS:** The Health hazards of this product should be low under normal industrial and commercial use.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Carbon Black	~ 0.58	1333-86-4
Silica, Amorphous	< 1.5	112926-00-8
Silica, Crystalline	< 2.2	14808-60-7

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.**SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists.**INGESTION:** Normally not needed. If large quantities are ingested, seek medical advice.**INHALATION:** No specific treatment is necessary since this material is not likely to be hazardous by inhalation.

SAFETY DATA SHEET

Date Prepared : 05/21/2015

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: May cause skin or eye irritation after repeated or prolonged contact.

SKIN: Substance may cause slight skin irritation.

SKIN ABSORPTION: None Expected.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide or foam. Treat as a petroleum fire.

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂, and hydrocarbons

EXPLOSION HAZARDS: None Expected.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus operated in pressure-demand mode, (NIOSH approved or equivalent) and full protective gear.

HAZARDOUS DECOMPOSITION PRODUCTS: If heated to decomposition, may emit toxic and/or irritating fumes.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb spilled material and place in appropriate container for disposal.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: May cause skin or eye irritation after repeated or prolonged contact.

HANDLING: Use of proper hygiene practices in the workplace is recommended.

STORAGE: Keep in a cool, well ventilated place

STORAGE TEMPERATURE: Store in a cool place below (120) F (49) C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Silica, Amorphous	TWA	20 mpp	80				
	STEL						
Silica, Crystalline	TWA	250mpp	10		0.025	NL	NL
	STEL					NL	NL

ENGINEERING CONTROLS: A system of local and/or general exhaust is recommended to keep employee exposures as low as possible.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Where contact with this material is possible, eye protection is recommended. May cause skin or eye

SAFETY DATA SHEET

Date Prepared : 05/21/2015

irritation after repeated or prolonged contact.

SKIN: Use of proper hygiene practices in the workplace is recommended.

RESPIRATORY: Good general ventilation should be sufficient to control airborne levels.

WORK HYGIENIC PRACTICES: May cause skin or eye irritation after repeated or prolonged contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Faint, characteristic odor.

APPEARANCE: Soft solid.

COLOR: Black

FLASH POINT AND METHOD: > (450°F) COC

FLAMMABLE LIMITS: 0 to 0

Notes: Not Established

AUTOIGNITION TEMPERATURE: Not Established

SPECIFIC GRAVITY: ~ 1.5

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: Will not occur.

STABILITY: Stable

HAZARDOUS DECOMPOSITION PRODUCTS: In case of fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

INCOMPATIBLE MATERIALS: Incompatible with strong solvents.

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

Chemical Name	NTP Status	IARC Status
Silica, Crystalline	1	1

12. ECOLOGICAL INFORMATION

GENERAL COMMENTS: Not Established

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of this product in accordance with all applicable local, state and federal regulations.

SAFETY DATA SHEET

Date Prepared : 05/21/2015

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not regulated

15. REGULATORY INFORMATION

UNITED STATES

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Carbon Black	1333-86-4
Silica, Crystalline	14808-60-7

CALIFORNIA PROPOSITION 65

Chemical Name	Wt.%	Listed
Carbon Black	~ 0.58	Cancer


16. OTHER INFORMATION

Date Prepared: 05/21/2015

HMIS RATING

HEALTH		0
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

NFPA CODES



MANUFACTURER DISCLAIMER: It does not relate to the use in combination with any other material or in any process. The data in this MSDS relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Design Engineering, Inc. The data on this sheet are related only to the specific material designated herein. Design Engineering, Inc. assumes no legal responsibility for use or reliance upon these data.